

REPLACED BY  
ART 34 AMDT

10

## CLAIMS

1. Fischer-Tropsch process for the conversion of carbon monoxide and hydrogen to  $C_5^+$  hydrocarbon mixtures in which process use is made of Fischer-Tropsch catalyst particles and fluid catalytic cracking catalyst particles.  
5
2. Process according to claim 1 wherein a reaction mixture of carbon monoxide and hydrogen is contacted with the Fischer-Tropsch catalyst particles and fluid catalytic cracking catalyst particles.  
10
3. Process according to claim 2 wherein the Fischer-Tropsch catalyst particles and the fluid catalytic cracking catalyst particles are dosed individually to the reaction mixture.  
15
4. Process according to claim 3 wherein the Fischer-Tropsch catalyst particles and the fluid catalytic cracking catalyst particles are dosed at different rates.
5. Process according to claim 2, wherein the Fischer-Tropsch catalyst particles and fluid catalytic cracking catalyst particles are used in the form of shaped bodies in which both particles are embedded.  
20
6. Process according to claim 1 wherein the Fischer-Tropsch catalyst particles are used in the second step of the Fischer-Tropsch process and the fluid catalytic cracking catalyst particles are used in the third step of the Fischer-Tropsch process.  
25
7. Process according to any one of the preceding claims wherein the Fischer-Tropsch catalyst particles comprise iron.  
30

REPLACED BY  
ART 34 AMDT

11

8. Process according to any one of the preceding claims wherein the Fischer-Tropsch catalyst particles comprise cobalt.
- 5 9. Process according to any one of the preceding claims wherein the fluid catalytic cracking catalyst is a spent or equilibrium fluid catalytic cracking catalyst.
- 10 10. Process according to any one of the preceding claims wherein a metal compound has been deposited on the fluid catalytic cracking catalyst.